

Accumulating Conveyors

Accumulating conveyors are general transport conveyors. They provide quiet operation, versatile design, and easy installation and maintenance. Model 138-ACC - 1-3/8 in. Dia. Roller, V-Belt Driven, Light Duty

- Bed - 6-1/2" deep x 12 ga. formed steel channel frame powder painted
- Rollers - 1-3/8" dia. x 18 ga. galvanized tread rollers spaced every 3" and 1-3/8" dia. x 18 ga. galvanized pressure roller spaced every 6"
- Overall frame widths: 12", 15", 18", & 24"
- Underside Drive (standard)
- Motor - 1/2 HP standard-3/4 HP available
- Adjustable Floor Supports Available
- Capacity - Maximum load per linear ft. of conveyor; 50 lbs., not to exceed rated capacities
- Finger tip pressure roller adjustment-no tools required
- Reversible Model 138-LRC - 1-3/8 in. Dia. Roller, V-Belt Driven Curve, Light Duty

- Bed - 6-1/2" deep x 12 ga. formed steel frame powder painted
- Rollers - 1-3/8" dia. x 18 ga. galvanized roller (12" to 18" OAW) and 2-1/2" dia. tapered to 1-11/16" dia. x 16 ga. galvanized, and 1.9" dia. x 16 ga. galvanized straight roller (24" OAW)
- Overall Frame Widths: 12", 15", 18", 24"
- Motor - 1/2 HP standard
- Adjustable Floor Supports Available
- Capacity - 150 lbs. (distributed load) Model 190-ACC - 1.9 in. Dia. Roller, V-Belt Driven, Medium Duty

- Bed - 6-1/2" deep x 12 ga. formed steel channel frame powder painted
- Rollers - 1.9" dia. x 16 ga. galvanized tread rollers spaced every 3" and 1.9" dia. x 16 ga. galvanized pressure rollers spaced every 6"
- Overall Frame Widths: 16", 18", 20", 22", 24", 26", 28", 30", 34", 36", 40", & 42"
- Underside Drive (standard)
- Motor - 1/2 HP standard-3/4 HP to 2 HP Available
- Adjustable Floor Supports Available
- Capacity - Maximum load per linear ft. of conveyor; 150 lbs., not to exceed rated capacities
- Finger tip pressure roller adjustment-no tools required
- Reversible Model 190-LRC - 1.9 in. Dia. Roller, V-Belt Driven Curve, Medium Duty

- Bed - 6-1/2" deep x 12 ga. formed steel frame powder painted
- Rollers - 2-1/2" dia. tapered to 1-11/16" dia x 16 ga. galvanized and 1.9" dia. x 16 ga. galvanized rollers
- Overall Frame Widths: 16", 18", 20", 22", 24", 26", 28", 30", 34", 36", 40", 42"
- Motor - 1/2 HP standard - 3/4 HP available
- Adjustable Floor Supports Available
- Capacity - 500 lbs. (distributed load) Model 190-ACZ - 1.9 in. Dia. Roller, Flat Belt Driven, Medium Duty

- Bed - 6-1/2" deep x 12 ga. formed steel channel frame powder painted
- Rollers - 1.9" dia. x 16 ga. galvanized tread rollers spaced every 3" and 1.9" dia. x 16 ga. galvanized pressure rollers spaced every 6"
- Overall Frame Widths: 16", 18", 20", 22", 24", 26", 28", 30", 34", 36", 40", & 42"
- Motor - 1/2 HP standard-3/4 to 2HP Available
- Reversible
- Center Drive (standard)

- Adjustable Floor Supports Available
- Capacity - Maximum load per linear ft. of conveyor; 200 lbs., not to exceed rated capacities