

Hydraulic Vertical Lifts -Series D

Series D Lift Offers High Quality and Safety, Low Maintenance, Features Exclusive Dual-Pak Design.

Guided Dual-Pak design has no cables, chains, bearings or other components that can break or require lubrication.

Carriage is lifted and lowered by dual 2" ram direct-acting hydraulic cylinders.

Lifts loads up to 3,000 lbs. Carriage sizes to 6' x 6'. Vertical rise heights to 14'. Ideal for mezzanine and balcony applications.

Pressure-compensated control valve regulates flow of hydraulic oil to ensure smooth, constant lowering speed under any load.

Ultra-high molecular weight polyethylene cylinder guide prevents cylinders from twisting during operation, improves cylinder life.

Pressure switch prevents the carriage from drifting or sinking to ensure smoother, safer loading and unloading operations.

Standard quick-connect cabling for push-button stations and gate interlocks is provided, significantly reducing field-wiring costs. (Check local codes for conformity.)

Remote mounted control panel and motor are prewired, ready for immediate installation.

Durable, high-quality construction ensures safe, reliable, long-term performance.

Meets ANSI/ASME B20.1 code.

As an option, the Pflow Series D Lift can be shipped as a self-contained unit equipped to service in-plant mezzanines. The Pflow Series D Mezzanine Lift is preassembled and shipped with lower-level enclosures and code-approved, safety gates. The lift motor pump and controls are prewired for fast, easy, one-day installation.